

OMR35HR0X

12NC/Fx: 859991659930

GTIN (EAN) code: 8003437939228

DIMENSION		UR
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	583	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	600	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	585	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	601	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	560	mm
Space in front, which is required to install bottom trim	9	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	Rear	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm
TALL CABINET (vent-shaft incoming)		•
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear	
Minimum space for inbound ventilation (tall cabinet)	40	mm
Minimum area for inbound ventilation cavity (tall cabinet)	150	cm ²
TALL CABINET (vent-shaft outgoing)	100	om
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Rear	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	150	cm
BASE CABINET (vent-shaft incoming)	100	onn
Indicates the position of the freespace for the inbound airflow (base cabinet)	Rear	
Minimum space for inbound ventilation (base cabinet)	40	mm
Minimum area for inbound ventilation cavity (base cabinet)	150	cm ²
BASE CABINET (vent-shaft outgoing)	150	CIII
Indicates the position of the freespace for the outbound airflow (base cabinet)	Rear	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	150	cm ²
	150	CIII

DIMENSION	MEAS	URE
APPLIANCE		
Height of the front	595	mm
Width of the front	595	mn
Depth of the front	20	mn
Maximum depth all protruding elements, e.g. handles, controls	47	mn
Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	55	mn
Projection of front in relation to housing of appliance	20	mn
Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	5	mn
When product panel is missing, set to 0	97	mn
Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	460	mn
Height from bearing area of appliances and lower handle	450	mn
Frontal handle thickness	30	mn
Frontal handle width	590	mn
MIN Height of the product body	570	mn
MAX Height of the product body	570	mn
Width of the product body	558	mn
Depth of the product body	548	mn
Full depth of product excluding protruding interface elements	570	mn
-	-	mn
Appliance can be used as base for other appliances from the same manufacturer. Default is "No	No	
Appliance Flap door		
Projection of the opened flap in relation to bearing area	0	mn
Maximum angle when flap door is opened totally	89	mn
Appliance Side swing door		
Lateral projection of front incl. controls when door is opened totaly. At the side where the hinge is mounted	0	mn
Lateral projection of opened front at the side where the hinge is fixed	0	mn
Maximum angle when door is opened totally	0	mn
Appliance other		
Depth from front end of the niche to the front end of the freespace of the retrace	428	mn
Height from niche to bottom end of freespace for the retrace	525	mn