

OMSR58CU1SB

12NC/Fx: 859991660270

GTIN (EAN) code: 8003437939563

DIMENSION	MEAS	UR
OVERALL CABINET		
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	583	mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	600	mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	585	mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	601	mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560	mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568	mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568	mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0	mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	560	mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	560	mm
Space in front, which is required to install bottom trim	9	mm
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes	
WALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear	
Minimum space or inbound ventilation (wall cabinet)	0	mm
Minimum area for inbound ventilation cavity (wall cabinet)	0	cm
WALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (wall cabinet)	Rear	
Minimum space or outbound ventilation (wall cabinet)	0	mm
Minimum area for outbound ventilation cavity (wall cabinet)	0	cm ²
TALL CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear	
Minimum space for inbound ventilation (tall cabinet)	40	mm
Minimum area for inbound ventilation cavity (tall cabinet)	150	cm²
TALL CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Rear	
Minimum space for outbound ventilation (tall cabinet)	0	mm
Minimum area for outbound ventilation cavity (tall cabinet)	150	cm
BASE CABINET (vent-shaft incoming)		
Indicates the position of the freespace for the inbound airflow (base cabinet)	Rear	
Minimum space for inbound ventilation (base cabinet)	40	mm
Minimum area for inbound ventilation cavity (base cabinet)	150	cm²
BASE CABINET (vent-shaft outgoing)		
Indicates the position of the freespace for the outbound airflow (base cabinet)	Rear	
Minimum space for outbound ventilation (base cabinet)	0	mm
Minimum area for outbound ventilation cavity (base cabinet)	150	cm²

leight of the front 595 Worth of the front 595 Waximum depth all protruding elements, e.g. handles, controls 42 wateral clearance between front edge and most protruding elements which avoid to open a eighbour front more than 90 degrees 600 projection of front in relation to housing of appliance 900 projection of front in relation to bearing area of the appliance. Taken at minimum height of projection of front in relation to bearing area of the appliance. Taken at minimum height of projection of front, which is required to guarantee full operability. The most protruding part gives this immension 460 minersion 460 mine	EASURE	
Avoid of the front 595 Depth of the front 20 Asximum depth all protruding elements, e.g. handles, controls 42 ateral clearance between front edge and most protruding elements which avoid to open a eleighbour front more than 90 degrees 700 pection of front in relation to housing of appliance 20 Projection of front in relation to bearing area of the appliance. Taken at minimum height of populance, if height is adjustable 80 When product panel is missing, set to 0 97 Bace in front, which is required to guarantee full operability. The most protruding part gives this 80 Beight from bearing area of appliances and lower handle 432 Brontal handle thickness 25 Brontal handle width 527 Bill Height of the product body 570 Bill Height of the product body 570 Bill depth of product body 558 Beight of the product body 558 Beight of the product body 548 Bill depth of product excluding protruding interface elements 570 Leight from bearing area of a base for other appliances from the same manufacturer. Default is "No" No suppliance Flap door 700 pection of the opened flap in relation to bearing area 0 Baximum angle when flap door is opened totally 89 Brontal Projection of front incl. controls when door is opened totally. At the side where the hinge is 0 Brontal Projection of front incl. controls when door is opened totally. At the side where the hinge is 0		
Depth of the front Asximum depth all protruding elements, e.g. handles, controls 42 ateral clearance between front edge and most protruding elements which avoid to open a eighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of publiance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this simension deight from bearing area of appliances and lower handle frontal handle thickness frontal handle width 527 MAX Height of the product body 570 MAX Height of the product body 584 Suppliance from product excluding protruding interface elements 570	mm	
Asximum depth all protruding elements, e.g. handles, controls ateral clearance between front edge and most protruding elements which avoid to open a eighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of ppliance, if height is adjustable When product panel is missing, set to 0 \$70 pace in front, which is required to guarantee full operability. The most protruding part gives this imension Beight from bearing area of appliances and lower handle Frontal handle thickness Frontal handle width Frontal handle	mm	
ateral clearance between front edge and most protruding elements which avoid to open a eighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of pipliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this imension deight from bearing area of appliances and lower handle frontal handle thickness rontal handle width AX Height of the product body AX Height of the product body for the product excluding protruding interface elements for the product excluding p	mm	
ateral clearance between front edge and most protruding elements which avoid to open a eighbour front more than 90 degrees Projection of front in relation to housing of appliance Projection of front in relation to bearing area of the appliance. Taken at minimum height of popliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this imension Height from bearing area of appliances and lower handle Height from bearing area of appliances and lower handle Height of the product body HAX Height of the product body HAX Height of the product body How the most protruding interface elements How the product body How the most protruding interface elements How the product body How the most protruding interface elements How the product body How the most protruding interface elements How the product body How the most protruding interface elements How the product body How the most protruding interface elements How the product body How the most protruding interface elements How the product body How the most protruding interface elements How the product body How the most protruding int	mm	
Projection of front in relation to bearing area of the appliance. Taken at minimum height of ppliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this imension delight from bearing area of appliances and lower handle frontal handle thickness rontal handle width 527 MIN Height of the product body MAX Height of the product body 570 MAX Height of the product body 548 Septh of the product excluding protruding interface elements 570	mm	
ppliance, if height is adjustable When product panel is missing, set to 0 Space in front, which is required to guarantee full operability. The most protruding part gives this imension deight from bearing area of appliances and lower handle deight from bearing area of appliances and lower handle deight from bearing area of appliances and lower handle deight from bearing area of appliances and lower handle deight from bearing area of appliances and lower handle deight from bearing area of appliances and lower handle deight from bearing area of appliances and lower handle deight from bearing area of appliances and lower handle deight from bearing area of appliances from the product body formula deight of the product body formula depth of the product body formula depth of product excluding protruding interface elements formula depth of product excluding protruding interface elements formula depth of product excluding protruding interface elements formula depth of product excluding protruding interface elements formula depth of product excluding protruding interface elements formula depth of product excluding protruding interface elements formula depth of product excluding protruding interface elements formula depth of product excluding protruding interface elements formula depth of product excluding protruding interface elements formula depth of product excluding protruding interface elements formula depth of the product body formula d	mm	
space in front, which is required to guarantee full operability. The most protruding part gives this limension delight from bearing area of appliances and lower handle frontal handle thickness frontal handle width frontal handle thickness frontal handle width frontal handle thickness frontal handle width frontal handle thickness frontal handle thickness frontal handle thickness frontal handle width frontal handle thickness frontal handle width frontal handle thickness frontal handle width frontal handle width frontal handle thickness frontal handle width frontal handle width frontal handle thickness frontal handle width frontal handle frontal handle width frontal handle width frontal handle	mm	
deight from bearing area of appliances and lower handle deight from bearing area of appliances and lower handle deight from bearing area of appliances and lower handle deight from bearing area of appliances and lower handle deight from bearing area of appliances and lower handle deight from bearing area of appliances some deight from the product body deight of the product excluding protruding interface elements deight from bearing area deight from the same manufacturer. Default is "No" deight of the product excluding protruding interface elements deight from bearing area deight from the same manufacturer. Default is "No" description of the opened flap in relation to bearing area defaximum angle when flap door is opened totally depliance Side swing door defaximum and projection of front incl. controls when door is opened totally. At the side where the hinge is nounted	mm	
Frontal handle thickness Frontal handle width Frontal handle wid	mm	
Frontal handle width ANA Height of the product body MAX Height of the product body Vidth of the product body Solveth of the product body Solveth of the product excluding protruding interface elements Solveth of the product excluding protruding interface elemen	mm	
MIN Height of the product body MAX Height of the product body State of the product excluding protruding interface elements State of the product excluding product excluding product excluding product elements State of the product excluding product excluding prod	mm	
MAX Height of the product body Vidth of the product body Septh of the product body Full depth of product excluding protruding interface elements S70	mm	
Vidith of the product body 548 Depth of the product body 548 Depth of the product excluding protruding interface elements 570	mm	
Deepth of the product body Full depth of product excluding protruding interface elements 570	mm	
full depth of product excluding protruding interface elements	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" No Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted	mm	
Appliance can be used as base for other appliances from the same manufacturer. Default is "No" Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted	mm	
Appliance Flap door Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted	mm	
Projection of the opened flap in relation to bearing area Maximum angle when flap door is opened totally Appliance Side swing door ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted		
Maximum angle when flap door is opened totally Appliance Side swing door ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted		
Appliance Side swing door ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted	mm	
ateral projection of front incl. controls when door is opened totaly. At the side where the hinge is nounted	mm	
nounted		
ateral projection of opened front at the side where the hinge is fixed 0	mm	
	mm	
Maximum angle when door is opened totally 0	mm	
Appliance other		
Depth from front end of the niche to the front end of the freespace of the retrace 428	mm	
Height from niche to bottom end of freespace for the retrace 525	mm	